PURITY Quell ST



Taste and function for gastronomy

Constant high performance in gastronomy is expected from high-quality machines. To ensure this performance is achieved at all times, it is advisable to work with optimised water.

The consistent water quality over the life of the filter and the reliable removal of unwanted taste and aroma elements ensures the best quality and optimum aroma development for your drinks, as well as high machine protection.

The benefits to you

- Removal of unwanted taste and aroma elements in the complete filtrate (including in the bypass water)
- Coffee develops its full aroma
- Targeted adaptation to local conditions with variable bypass setting
- Limescale deposits and associated machine breakdowns are reduced
- Service and repair costs are clearly reduced





BRITA Professional Filter Service App

The Filter Service App is your ideal assistant. This unique, comprehensive tool helps determine the right type and size of filter for your precise needs. It provides detailed installation guidance for service engineers, calculates when cartridges will need replacing and has a wealth of other, innovative capabilities.





Or visit https://professional.brita.net/app



Systematic filter technology

1 Pre-filtration

A fleece at the inlet reliably retains coarse particles and, with its laminar water distribution, ensures a high utilisation of the downstream filter medium.

Carbonate hardness reduction

The PURITY Quell ST filter medium reduces the content of carbonate hardness in a targeted way. As a result, unwanted limescale formation is prevented.


3 Activated carbon filtration

All of the water - including the bypass water runs through an activated carbon filter. Taste and aroma elements that have a negative affect do not enter the filtrate

Fine filtration

Comparable capacity

At the end of the filtration process a fleece retains any fine particles.



The illustration serves as explanation of the filter technology. It is not to scale.

Quality and safety

Optimum water quality

Outstanding and consistent water quality - free of unwanted taste and aroma elements.

Maximum product safety

For uninterrupted operation and safe use.

Simple to use

Operation is simpler and easier than ever.

The food safety of BRITA Professional water filter products is tested and monitored by independent institutes.





4,4201







7,2531



*applies to all materials in contact with water

PURITY Quell ST	450	600	1200			
Technology	decarbonisation					
Capacity¹ coffee /espresso /vending machines (at a carbonate hardness of 10 °dH/bypass setting of 40 %)	4,2171	7,2071	13,1871			
Comparable capacity according to DIN 18879-1:2007: The comparable capacity is a standardised indicator to facilitate comparison of different filters. The comparable capacity is determined under extreme conditions. Normally the usable capacity in practical operation is clearly higher than the comparable capacity						

and may vary greatly depending on the usage conditions

2,2401

	_,	.,	.,		
Max. operating pressure	6.9 bar				
Water intake temperature	4-30°C				
Flow rate with 1 bar pressure loss	max. 3501/h				
Nominal flow	601/h 1201/h		DI/h		
Pressure loss at nominal flow	max. 0.12 bar	max. 0.36 bar	max. 0.32 bar		
Dimensions (height/width)	408/249 mm	520/249 mm	550/288 mm		
Weight (dry/wet)	10/12 kg	12/15 kg	18/24 kg		
Connections (input / output)	G 1" G 3/4"				
Operating position	horizontal and vertical				
Operation	Use after inhouse softening units possible				
PURITY Quell ST	Order number				
New filter (complete system with filter cartridge) with measuring and display unit	1009227	1009229	1009231		
New filter (complete system with filter cartridge) without measuring and display unit	1009228	1009230	1009232		
Replacement cartridge	273000	273200	273400		
Accessories	Order number				
BRITA FlowMeter 10 - 100	1033041				
BRITA FlowMeter 100 - 700	1033042				
Carbonate hardness test kit	710800				
propriate hoses and hose sets from our comprehensive FlexConnect range as well as other accessories can be found in our price list.					
Replacement parts	Order number				

	Replacement parts	Order number		
	Pressure vessel lid with measuring and display unit	272000²	272400	
	Pressure vessel lid without measuring and display unit	272100	-	
		1 The capacities given have been tested and calculated on the basis of	f normal application and machi	

Explanatory notes

conditions. Due to external influences (e.g. variations in raw water quality and/or machine type), deviations from these results can occur.

² These order numbers relate to P1200

Only drinking quality water may be used as the water supply for BRITA water filters

For more information please contact:

BRITA Water Filter Systems Ltd.

BRITA House | 9 Granville Way | Bicester | OX26 4JT | United Kingdom Tel.: +44 844 742-4990 | Fax: +44 186 936-5962

BRITA Water Filter Systems Distributors Pty Ltd

Suite 2, Level 9, 123 Epping Road | Macquarie Park, NSW, 2113 | Australia Tel.: +61 1300 955-021 | NZ: 0800 482-008 professional@brita.com.au | www.brita.com.au

Headquaters: BRITA SE

Heinz-Hankammer-Straße 1 | 65232 Taunusstein | Germany Tel.: +49 6128 746-0 | Fax: +49 6128 746-5033 info@brita.net | www.brita.net

BRITA Recycling Program

the BRITA corporate philosophy. As early as 1992, we established a recycling programme for our filter



brita.co.uk/recycling-professional